

ARI-SAFE TC - EN ISO 4126-1

Reference	Cross-section drawing	Data sheet	Operating instruction	CAD	Chemical resistance
-----------	-----------------------	------------	-----------------------	-----	---------------------



941

ARI-SAFE TC - EN ISO 4126-1

Application :

Industrial installations, processing technology, plant manufacturing, etc.

Medium :

Steam, neutral gases, vapours and liquids

Application (Stainless Steel) :

Industrial installations, processing technology, plant manufacturing, etc.

Medium (Stainless Steel) :

Steam, aggressive gases, vapours and liquids


eClass-No.:

37010905


S = Spare part drawing

A = Approvals

Figure	PN	DN	Material	Connection	Form	Temperature *body	Variation
S A	25941	PN 40 DN 15-DN 20	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet closed lifting device
S A	25941	PN 40 DN 25-DN 25	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet closed lifting device
S A	25942	PN 40 DN 15-DN 20	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet open lifting device
S A	25942	PN 40 DN 25-DN 25	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet open lifting device
S A	25943	PN 40 DN 15-DN 20	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet gastight cap
S A	25943	PN 40 DN 25-DN 25	EN-GJS-400-18U-LT, EN-JS1049	screwed socket	Angle pattern	-10 °C to 350 °C	closed bonnet gastight cap
S A	55941	PN 40 DN 15-DN 20	GX5CrNiMo19-11-2, 1.4408	screwed socket	Angle pattern	-60 °C to 400 °C	closed bonnet closed lifting device
S A	55941	PN 40 DN 25-DN 25	GX5CrNiMo19-11-2, 1.4408	screwed socket	Angle pattern	-60 °C to 400 °C	closed bonnet closed lifting device
S A	55943	PN 40 DN 15-DN 20	GX5CrNiMo19-11-2, 1.4408	screwed socket	Angle pattern	-60 °C to 400 °C	closed bonnet gastight cap
S A	55943	PN 40 DN 25-DN 25	GX5CrNiMo19-11-2, 1.4408	screwed socket	Angle pattern	-60 °C to 400 °C	closed bonnet gastight cap



941



942



943



ARI-SAFE TC - EN ISO 4126-1

Figure Description

941	Full lift/Standard safety valve with thread connection - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1
942	Full lift/Standard safety valve with thread connection - closed bonnet - open lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1
943	Full lift/Standard safety valve with thread connection - closed bonnet - gastight cap - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1