

Return liquid temperature limiter

Cross-section drawing

Data sheet



650

Return liquid temperature limiter

Application :


Return temperature limitation for a pipe tracing system.

Medium :


Steam, condensate, etc.

A = Approvals


| Figure | PN | DN | Material | Connection | Form | Temperature *body | Variation |
|-----------|-------|-------------|-----------------|----------------|------------------|----------------------|-----------|
| A 45650-1 | PN 40 | DN 15-DN 25 | P250 GH, 1.0460 | flanged | Straight through | -60 °C to 180 °C | Standard |
| A 45650-2 | PN 40 | DN 15-DN 25 | P250 GH, 1.0460 | screwed socket | Straight through | -60 °C to 180 °C | Standard |
| A 45650-3 | PN 40 | DN 15-DN 25 | P250 GH, 1.0460 | socket end | Straight through | -60 °C to 180 °C | Standard |
| A 45650-4 | PN 40 | DN 15-DN 25 | P250 GH, 1.0460 | butt weld end | Straight through | -60 °C to 180 °C | Standard |




650,650-1



650-2



650-3



650-4

Return liquid temperature limiter

| Figure | Description |
|--------|---|
| 650 | Liquid return temperature limiter |
| 650-1 | Liquid return temperature limiter with flanges |
| 650-2 | Liquid return temperature limiter with screwed socket |
| 650-3 | Liquid return temperature limiter with socket weld ends |
| 650-4 | Liquid return temperature limiter with butt weld ends |