



SA 07.1, SAR 07.1, SA ExC 07.1, SAR ExC 07.1, SA 07.5, SAR 07.5, SA ExC 07.5

Multiturn electric actuators AUMA

Application : Industrial installations, processing technology, plant manufacturing, etc.

A = Approvals

Type	Voltage	Drehmoment	Temperaturr (perm. ambient temperature)
A SA 07.1	400V, 50Hz 3~	30 Nm	-25 °C to 80 °C
A SA 07.5	400V, 50Hz 3~	60 Nm	-25 °C to 80 °C
A SA 10.1	400V, 50Hz 3~	120 Nm	-25 °C to 80 °C
A SA 14.1	400V, 50Hz 3~	250 Nm	-25 °C to 80 °C
A SA ExC 07.1	400V, 50Hz 3~	30 Nm	-20 °C to 40 °C
A SA EXC 07.5	400V, 50Hz 3~	60 Nm	-20 °C to 40 °C
A SA ExC 10.1	400V, 50Hz 3~	120 Nm	-20 °C to 40 °C
A SA ExC 14.1	400V, 50Hz 3~	250 Nm	-20 °C to 40 °C
A SAR 07.1	400V, 50Hz 3~	Nm	-25 °C to 60 °C
A SAR 07.5	400V, 50Hz 3~	Nm	-25 °C to 60 °C
A SAR 10.1	400V, 50Hz 3~	Nm	-25 °C to 60 °C
A SAR 14.1	400V, 50Hz 3~	Nm	-25 °C to 60 °C
A SAR ExC 07.1	400V, 50Hz 3~	Nm	-20 °C to 40 °C
A SAR EXC 07.5	400V, 50Hz 3~	Nm	-20 °C to 40 °C
A SAR ExC 10.1	400V, 50Hz 3~	Nm	-20 °C to 40 °C
A SAR ExC 14.1	400V, 50Hz 3~	Nm	-20 °C to 40 °C