

Electric actuator FR 2.1 / FR 2.2


[Cross-section drawing](#)[Data sheet](#)[Operating instruction](#)[CAD](#)

Electric actuator FR 2.1 / FR 2.2

Application : Industrial installations, processing technology, plant manufacturing, etc.

A = Approvals

Type	Voltage	Thrust force	Control speed	Travel	Temperaturr (perm. ambient temperature)
A FR2.1	230V, 50/60Hz 1~	0,9 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C
A FR2.1	24V, 50/60Hz 1~	0,9 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C
A FR2.1	110V, 50/60Hz 1~	0,9 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C
A FR2.2	230V, 50/60Hz 1~	2,2 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C
A FR2.2	24V, 50/60Hz 1~	2,2 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C
A FR2.2	110V, 50/60Hz 1~	2,2 kN	0,29 mm/sec.	35 mm	0 °C to 50 °C



FR 2.1,FR 2.2

Electric actuator FR 2.1 / FR 2.2

Figure

Description

FR 2.1

Electric actuator FR 2.1

FR 2.2

Electric actuator FR 2.2